

Agriculture Technical School, Hiwara Gondia

(Dr. Panjabrao Dheshmukh Krishi Vidhyapeeth Akola)

Email: ats_gondia@rediffmail.com



No.ATS/Hiwara/ Quotation Notice/ 69/2026

Date: 02 / 06 /2026

Quotation Notice

To,

-
-
-

Subject :- Quotation for Providing Shed for Sericulture unit under A.T.S. at Dr. P.D.K.V., Akola.

महोदय,

वरिल विषयाच्या अनुषंगाने आपणास कळविण्यात येते की, कृषि तंत्र विद्यालय हिवरा, गोंदिया येथील 'रेशिम अळी संगोपन निवारा' (Shed For Sericulture) तयार करणे आहे, सदर कामे खालील नमुद केल्या प्रमाणे आहेत तरी यासंबंधीचे दर पत्रक प्राचार्य कृषि तंत्र विद्यालय हिवरा, गोंदिया यांचे नावे दि. १२/०६/२०२६ पर्यंत (कार्यालयीन वळेत) पाठविण्यात यावे. उशीरा प्राप्त झालेल्या निविदांचा विचार केला जाणार नाही.

Item No.	Particulars of Item	Qty.	Rate	Unit	Amount
1	Excavation for foundation in earth, soil of all types, sand, gravel and soft murum, including removing the excavated material up to a distance of 50 m. beyond the building area and stacking and spreading as directed, dewatering, preparing the bed for the foundation and necessary back filling, ramming, watering including shoring and strutting etc. complete. (Lift upto 0.00 to 1.50 m.) By Manual Means	8.39		Cum	
2	Filling in plinth and floors with contractors material/brought from outside and approved by Engineer incharge in layers of 15 cm to 20 cm including watering and compaction etc. complete	4.66		Cum	
3	Providing and laying Cast in situ/Ready Mix cement concrete in M-10 of trap/granite/ quartzite/ gneiss metal for foundation and bedding including bailing outwater, Steel centering, formwork, laying/pumping, compacting, roughening them if special finish is to be provided, finishing if required and curing complete, with fullyautomatic micro processor based PLC with SCADA enabled reversible Drum Typemixer/concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate(Crushed sand VSI Grade)	3.62		Cum	
4	Providing second class Burnt Brick masonry with conventional/ I.S. type bricks in cement mortar 1:6 in foundations and plinth of inner walls/ in plinth external walls including bailing out water manually .	2.47		Cum	

K. Jant
Principal

Agriculture Technical School
Hiwara, Gondia

	striking joints on unexposed faces, raking out joints on exposed faces and watering etc. Complete			
5	Providing second class Burnt Brick masonry with conventional/ I.S. type bricks in cement mortar 1:6 in superstructure including striking joints, raking out joints, watering and scaffolding etc. Complete	2.34	Cum	
6	Providing and laying Cast in situ/Ready Mix cement concrete in M20 of trap/ granite/quartzite/gneiss metal for bed blocks, foundation blocks and such other items including bailing out water, Steel centering, formwork, laying/ pumping, compacting, roughening them if special finish is to be provided, finishing uneven and honeycombed surface and curing etc. complete. The Cement Mortar 1:3 plaster is considered for rendering uneven and honeycombed surface only. Newly laid concrete shall be covered by gunny bag, plastic, tarpaulin etc. (Wooden centering will not be allowed.), with fully automatic micro processor based PLC with SCADA enabled reversible Drum Type mixer/ concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate (Crushed sand VSI Grade	0.39	Cum	
7	Providing internal cement plaster 20mm-thick in Single coats in cement mortar 1:5 without neeru finish, to concrete, brick surface, in all positions including scaffolding and curing etc. complete	60.76	Sqm	
8	Providing structural steel work of rectangular hollow steel section for steel trusses, other similar trussed items like purlin and members with all bracing, gusset plates etc. as per detailed designs and drawings or as directed including cutting, fabricating, hoisting, erecting, fixing in position making riveted/bolted/ welded connections and one coat of anticorrosive paint and over it two coats of oil painting of approved quality and shade complete	0.94	MT	
9	Providing and fixing colour coated Zinalume (R) AZ150 (min 150 gms/sq.mt. total on each side) profiled sheets for roofing. The feed material is manufactured out of nominal 0.45 mm Base Metal Thickness (BMT) (0.5 mm TCT), Hi-strength steel with min.550 MPa yield strength, metallic hot dip coated with Aluminium-Zinc alloy (55% aluminium 43.4% zinc 1.6% silicon) with COLORBOND (R) steel quality super durable polyester paint coat (with inorganic pigment). The paint shall have a total coating thickness of nominal 35 um, comprising of nominal 25 um exterior coat on top surface and nominal 10 um reverse coat on back surface. Profile sheet shall have nom. 950-1050 mm effective cover width and nominal 25-30 mm deep ribs with subtle square fluting in the five pan at nominal 180-250 mm center-to-center. The end rib shall be designed for anti-capillary groove. and return leg. The feed material should have coil manufacturers product details marked a regular interval. Including fasteners with min.fastened with min. 25 um Zinc-Tin alloy coated, Hex head, self-drilling screw etc. complete. (weight of profile 4.52 Kilogram/ One Square Metre)	38.64	Sqm	
10	Providing and fixing of colour coated Zinaluminium(R) AZ150 (min 150 gms/sq.mt. total on each side) profiled sheets for roofing. The feed material is manufactured out of nominal 0.45 mm Base Metal Thickness (BMT) (0.5 mm TCT), Hi-strength steel with min.550 MPa yield strength, metallic hot dip coated withAluminium-Zinc alloy (55% aluminiumm 43.4% zinc 1.6% silicon) with COLORBOND (R) steel quality super durable polyester paint coat (with inorganic pigment). The paint shall	7.00	RMT	

K. Gant
Principal

	have a total coating thickness of nominal 35 mm, comprising of nominal 25mm exterior coat on top surface and nominal 10 um reverse coat on back surface. Profile sheet shall have nom. 950-1050 mm effective cover width and nominal 25-30 mm deep ribs with sublet square fluting in the five pan at nominal 180-250 mm center-to-center. The end rib shall be designed for anti-capacity groove. and return leg. The feed material should have coil manufacturers product details marked a regular interval. including fasteners with min. fastened with min. 25 um Zinc-Tin alloy coated, Hex head, self-drilling screw etc. complete. (weight of profile 4.52 Kilogram/ One Square Metre) 600 mm girth (Surface Width)			
11	Providing and applying three coats of water proof cement paint of approved manufacture and of approved colour to old plastered surfaces including scaffolding if necessary, cleaning and preparing the surface, watering for two days etc. complete.	60.76	Sqm	
12	Providing and fixing in position Chainlink fencing having size 50x50 of 10 gaouge on M.s. pipe & over 35x4 mm m.s. flat with welding ect. Complete.	45.52	Sqm	

अटि व शर्ती :-

१. दरपत्र हे प्राचार्य कृषि तंत्र विद्यालय हिवरा, गोंदिया यांचे नावे देण्यात यावे.
२. दरपत्रक कार्यालयीन वेळेत स्विकारल्या जातील.
३. सदर दरपत्रकातील सर्व दर दि. ०२/०६/२०२६ ते ३१/१२/२०२६ या कालावधी करिता राहतील.
४. दरपत्रके स्विकारण्याचे अथवा नाकारण्याचे सर्व अधिकार प्राचार्य कृषि तंत्र विद्यालय हिवरा, गोंदिया यांनी राखून ठेवले आहेत.

K. Gant...
Principal
Agriculture Technical School
Hiwara, Gondia