



डॉ.पंजाबराव देशमुख कृषि विद्यापीठ, अकोला

कृषि विज्ञान केंद्र

सेलसुरा ता.जि.वर्धा - ४४२९०९ (महाराष्ट्र)



डॉ.जिवन रा. कतोरे
वरीष्ठ शास्त्रज्ञ व प्रमुख

Email-kvkselsura@pdkv.ac.in / kvk.wardha@gmail.com

जा.क्र.कृविके/सेलसुरा/११७/ २०२६

दिनांक २९ /४ / २०२६

निविदा मागणी पत्र

प्रति

- १)
- २)
- ३)

विषय :- कार्यालयीन प्रक्षेत्रावर शेती संबंधीत साहित्य ठेवणेकरिता लोखंडी दोन शेड प्रत्येकी (४० x २०) फुट आकाराचे सिमेंट काँक्रीटची पायाबांधणी करून शेड उभारण्याकरिता दर मागविणेबाबत.

उपरोक्त विषयाचे अनुषंगाने कृषि विज्ञान केंद्र, सेलसुरा येथील कार्यालयाचे प्रक्षेत्रावर शेती संबंधीत साहित्य ठेवण्याकरिता ठेवणेकरिता लोखंडी दोन शेड प्रत्येकी (४० x २०) फुट आकाराचे सिमेंट काँक्रीटची पायाबांधणी करून शेड उभारणी करणे आवश्यक आहे. त्याकरिता खालील प्रमाणे दर कळविण्यात यावे.

Name of work :- Erection of Implement Shed at Krishi Vigyan Kendra Selsura Dist. Wardha Under Dr. PDKV Akola.					
Item No.	Particulars of Item	Qty.	Rate	Unit	Amount
1	Excavation for foundation in hard murum including removing the excavated material upto distance of 50 metres beyond the building area and stacking and spreading as directed, dewatering, preparing the bed for the foundation and necessary back filling, ramming, watering including shoring and strutting etc. complete. (Lift upto 1.50m) By Manual / Machines Means	0.66		Cum	
2	Providing and laying cast in situ / Ready Mix Cement Concrete M- 20 RCC single rim bored pile of 225 mm dia. each of load capacity as per design and of specified diameter of pile and bulb as directed, sunk to the required depth through all strata except rock, excluding provision of reinforcement including placing with fully automatic micro processor based PLC with SCADA enabled reversible Drum Type mixer/ concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate (Crushed sand VSI Grade) by tremie arrangement, compaction of concrete including chipping and dressing including chipping and dressing if required etc. complete. (Excluding steel reinforcement)	18.00		Rmt	

3	Providing and laying Cast in situ/Ready Mix cement concrete in M20 of trap/ granite/quartzite/gneiss metal for bed blocks, foundation blocks and such other items including bailing out water, Steel centering, formwork, laying/ pumping, compacting, roughening them if special finish is to be provided, finishing uneven and honeycombed surface and curing etc. complete. The Cement Mortar 1:3 plaster is considered for rendering uneven and honeycombed surface only. Newly laid concrete shall be covered by gunny bag, plastic, tarpaulin etc. (Wooden centering will not be allowed.), with fully automatic micro processor based PLC with SCADA enabled reversible Drum Type mixer/ concrete Batch mix plant (Pan mixer) etc. complete. With fine aggregate (Crushed sand VSI Grade)	0.77		Cum	
4	Providing and fixing in position TMT - FE - 500 bar reinforcement of various diameters for R.C.C. pile caps, footings, foundations, slabs, beams columns, canopies, staircase, newels, chajjas, lintels pardis, copings, fins, arches etc. as per detailed designs, drawings and schedules. including cutting, bending, hooking the bars, binding with wires or tack welding and supporting as required complete.	0.12		MT	
5	Providing and fabricating structural steel work in rolled sections like joists, channels, angles, tees etc. as per detailed design and drawings or as directed including cutting, fabricating, hoisting, erecting, fixing in position making riveted / bolted /welded connections without connecting plates, braces etc. and including one coat of anticorrosive paint and over it two coats of oil painting of approved quality and shade etc. complete	0.20		MT	
6	Providing and fixing colour coated Zinalume (R) AZ150 (min 150 gms/sq.mt. total on each side) profiled sheets for roofing. The feed material is manufactured out of nominal 0.45 mm Base Metal Thickness (BMT) (0.5 mm TCT), Hi-strength steel with min.550 MPa yield strength, metallic hot dip coated with Aluminium-Zinc alloy (55% aluminium 43.4% zinc 1.6% silicon) with COLORBOND (R) steel quality super durable polyester paint coat (with inorganic pigment). The paint shall have a total coating thickness of nominal 35 um, comprising of nominal 25 um exterior coat on top surface and nominal 10 um reverse coat on back surface. Profile sheet shall have nom. 950-1050 mm effective cover width and nominal 25-30 mm deep ribs with subtle square fluting in the five pan at nominal 180-250 mm center- to-center. The end rib shall be designed for anti-capillary groove. and return leg. The feed material should have coil manufacturers product details marked a regular interval. Including fasteners with min. fastened with min. 25 um Zinc-Tin alloy coated, Hex head, self- drilling screw etc. complete. (weight of profile 4.52 Kilogram/ One Square Metre)	144.00		Sqm	

7	<p>Providing and fixing of colour coated Zinc aluminium(R) AZ150 (min 150 gms/sq.mt.total on each side) profiled sheets for roofing. The feed material is manufactured out of nominal 0.45 mm Base Metal Thickness (BMT) (0.5 mm TCT), Hi-strength steel with min.550 MPa yield strength, metallic hot dip coated with Aluminium-Zinc alloy (55% aluminium 43.4% zinc 1.6% silicon) with COLORBOND (R) steel quality super durable polyester paint coat (with inorganic pigment). The paint shall have a total coating thickness of nominal 35 mm, comprising of nominal 25mm exterior coat on top surface and nominal 10 um reverse coat on back surface. Profile sheet shall have nom. 950-1050 mm effective cover width and nominal 25-30 mm deep ribs with sublet square fluting in the five pan at nominal 180-250 mm center- to-center. The end rib shall be designed for anti-capacity groove. and return leg. The feed material should have coil manufacturers product details marked a regular interval. including fasteners with min. fastened with min. 25 um Zinc-Tin alloy coated, Hex head, self-drilling screw etc. complete. (weight of profile 4.52 Kilogram/ One Square Metre) 600 mm girth (Surface Width)</p>	12.80		Rmt	
---	---	-------	--	-----	--

अटी व शर्ती

- १) सिलबंद दरपत्रक या कार्यालयास दि.५/५/२०२६ ला सायंकाळी ५.०० पर्यंत पाठविण्यात याव्यात त्यानंतर प्राप्त निविदांचा विचार केला जाणार नाही. तसेच लिफाफ्यावर वरीष्ठ शास्त्रज्ञ व प्रमुख, कृषि विज्ञान केंद्र, सेलसुरा जि.वर्धा यांचे नावाने पाठविण्यात याव्यात
- २) लोखंडी शेडचे पूर्ण काम झाल्यानंतरच देयक अदा करण्यात येईल. याकरीता कोणतीही अग्रीम राशी मिळणार नाही.
- ३) दर स्विकारणे अथवा नाकारणे याचे सर्व अधिकार वरीष्ठ शास्त्रज्ञ व प्रमुख, कृषि विज्ञान केंद्र, सेलसुरा जि.वर्धा यांच्याकडे राखीव असतील.

PSJ

वरीष्ठ शास्त्रज्ञ व प्रमुख
कृषि विज्ञान केंद्र, सेलसुरा