

QUOTATION NOTICE

No. SRS/SOR/Quo /490/2021
Office of the Senior Research Scientist
Sorghum Research Unit, Dr. P.D.K.V., Akola
Date: 19/ 01 /2021

Subject : - Invitation of Quotation for Supply of ROTAVATOR of 7 feet for 57 HP Tractor and 3.5 feet for 28 HP Tractor for Sorghum Research Unit, Dr. PDKV, Akola.

You are invited to submit your most competitive quotation for the following services in the format attached herewith only as Annexure-A:-

Sr. No.	Particulars	Specifications	Approximate Quantity Required
1	7 feet Rotavator for 57 HP Tractor (Maschio Gaspardo Rotavator V – Plus 205 make)	Facility of tractor PTO operated mechanism for Rotavator, three point type of hitch attachment/Linkage, 55 hp to 60 hp power range, Multi Speed type of gear box used, Gear type of Side Transmission Drive, Spur types of gear used, Availability of chain/Gear cover part for safety, PTO speed required in 540 rpm, Rotor Speed in 258 rpm (with ± 10 rpm tolerance), L-Shape of Cutting Blade, Plane type of cutting edge of blade, 40 to 55 HRC hardness of Edge portion, 40 to 55 HRC hardness on Shank portion, Total 60 number of blade on rotor, 06 Number of blade per Flange, 09 Number of flange in rotor shaft, roller types of bearing used, capable to tillage both wet and dry soil land, Availability of Adjustable Depth Skids, Rotavator Stand shall be provided, Rotavator Shield to prevent flying of mud & stone shall be provided, Facility Side Disc assembly, Guard over propeller shaft shall be provided, Availability of lubrication system, one year warranty, Rotavator frame and Blades must be Rust Proof, Diameter of rotar shaft in 90 mm (with ± 2 mm tolerance), Rotor Diameter (including flange & blade mounted on flange) in 480 mm, Cutting Blade thickness in 7 mm, Cutting blade width in 80 mm, Orientation of blade in 35 degree, Length of blade along the flange in 175	1 Unit

		mm, Length of blade along the rotor shaft in 135 mm, Distance between consecutive flanges in 250 mm (with ± 2 mm tolerance), Working width by rotavator in 84 inches, Working depth by rotavator in 5 inches, Depth of puddle in wet land operation in 200 mm, Size of rotavator (Lx W x H) in 30.5 X 88 X 44.3 inches, Weight of Rotavator in 470 Kg	
2	3.5 feet Rotavator for 28 HP Tractor (Maschio Gaspardo Rotavator W-105 make)	Facility of tractor PTO operated mechanism for Rotavator, three point type of hitch attachment/Linkage, 28 hp power range, Multi Speed type of gear box used, Gear type of Side Transmission Drive, Spur types of gear used, Availability of chain/Gear cover part for safety, PTO speed required in 540 rpm, Rotor Speed in 258 rpm (with ± 10 rpm tolerance), L-Shape of Cutting Blade, Plane type of cutting edge of blade, 40 to 55 HRC hardness of Edge portion, 40 to 55 HRC hardness on Shank portion, Total 36 number of blade on rotor, 06 Number of blade per Flange, 09 Number of flange in rotor shaft, roller types of bearing used, capable to tillage both wet and dry soil land, Availability of Adjustable Depth Skids, Rotavator Stand shall be provided, Rotavator Shield to prevent flying of mud & stone shall be provided, Facility Side Disc assembly, Guard over propeller shaft shall be provided, Availability of lubrication system, one year warranty, Rotavator frame and Blades must be Rust Proof, Diameter of rotar shaft in 90 mm (with ± 2 mm tolerance), Rotor Diameter (including flange & blade mounted on flange) in 480 mm, Cutting Blade thickness in 7 mm, Cutting blade width in 80 mm, Orientation of blade in 35 degree, Length of blade along the flange in 175 mm, Length of blade along the rotor shaft in 135 mm, Distance between consecutive flanges in 250 mm (with ± 2 mm tolerance), Working width by rotavator in 84 inches, Working depth by rotavator in 5 inches, Depth of puddle in wet land operation in 200 mm, Size of rotavator Width 49.2 inches, Weight of Rotavator in 340 Kg	1 Unit

II. Terms and conditions of supply :

1. The quotation should be in the name of "Senior Research Scientist (Sorghum), Dr.P.D.K.V., Akola 444 104 (M.S.)".
2. Mention on envelop as "**Quotation for Supply of ROTAVATOR of 7 feet for 57 HP Tractor and 3.5 feet for 28 HP Tractor separately.**"
3. The quotation should reach in this office on or before : **28/ 01/2021**
4. The quotation will be accepted on all working days between 10.30 to 5.30pm.
5. The rates quoted will have to be inclusive of all taxes with delivery at Sorghum Research Unit, Dr. P.D.K.V., Akola.
6. The rates quoted will have to be accepted for a period of six months from the date fixed for opening the quotation.
7. The right to accept whole or part of the quotation or reject is reserved with the undersigned without assigning reason there.
8. The material will have to be supplied as per specification within **15 day** from the date of Supply order.
9. In the event of failure to supply the material within the specified period, the undersigned will be authorized to cancel / extend the order of supply.
10. The payment will be done after supply of material in good condition. No advance payment. The payment will be made through bank only.
11. It is essential to mention the sales GST No., Registration No. Of the supplier firm.
12. Quotation should be submitted in the given format.



**Senior Research Scientist
Sorghum Research Unit
Dr. P.D.K.V, Akola**

FORMAT OF QUOTATION FOR SUPPLIER

ANNEXURE - A

Sr. No.	Brief Description of the Services	Specifications	Qty.	Unit	Quoted Unit Rate in Rs.	Total Amount
						Rupees
Any other charges, if any						
Total	In Figures					
	In Words					
GST						

Gross Total Cost : Rs

We agree to supply the above services in accordance with the technical specifications for a total contract price of Rs. (Amount in figure) Rs. (Amount in words) within the period specified in the Invitation for Quotation.

We also confirm that the normal commercial warrantee/ guarantee of Months shall apply to the offered services.

We hereby certify that we have neither black-listed by Dr. PDKV., Akola nor any other Govt. organization.

We hereby certify that we have no "Conflict of Interest" with **SorghumResearch Unit, Dr. PDKV, Akola** office of staff.

We hereby certify that we have taken steps to ensure that no person acting for us or on our behalf will engage in corrupt, fraudulent, collusive, or obstructive practices (as defined in the prevailing World Bank's sanction procedures) in competing for or in performing the Contract.

Signature of Supplier

***Supplier should also mention the discount offered.**